

114 Series Multi-Flex™ Medium Duty Plugs Sizes: 1.7" to 84" Without By-Pass

Pipe Diameter				Maximum Inflation		**Pipeline Max. Head		Inflation Port*	Deflated Length		Shpg Wt lbs	Item Number
Maximum in	Minimum in	Maximum in	Minimum in	psig	bar	ft	m		in	mm		
2	51	1.7	44	30	2.1	35	10.6	1/2 M - 1/4 QC	10.5	266	2	114-002
3	76	2	51	30	2.1	35	10.6	1/2 M - 1/4 QC	14	356	2	114-003
4	102	2.5	64	30	2.1	35	10.6	1/2 M - 1/4 QC	16	406	3	114-004
6	152	3	77	30	2.1	35	10.6	1 M - 1/4 QC	19	482	6	114-006
8	203	3.5	89	30	2.1	35	10.6	1 M - 1/4 QC	21	533	6	114-008
10	254	3.5	89	30	2.1	35	10.6	1 M - 1/4 QC	26	660	7	114-010
12	305	4.5	115	25	1.7	29	8.8	1 1/2 M - 1/4 QC	30	762	11	114-012
15	381	5.5	140	25	1.7	29	8.8	2 M - 1/2 QC	34	864	16	114-015
16	406	5.5	140	25	1.7	29	8.8	2 M - 1/2 QC	41	1041	22	114-016
18	457	6	153	22	1.5	25	7.7	2 M - 1/2 QC	45	1143	24	114-018
20	508	6	153	20	1.4	23	7.9	2 M - 1/2 QC	50	1270	25	114-020
24	610	6	153	10	0.7	12	3.5	2 M - 1/2 QC	59	1498	28	114-024
30	762	6	153	9	0.6	10	3.2	2 M - 1/2 QC	73	1854	34	114-030
33	838	7	178	9	0.6	10	3.2	2 M - 1/2 QC	74	1879	36	114-033
36	914	7	178	9	0.6	10	3.2	2 M - 1/2 QC	84	2133	40	114-036
42	1067	8	204	9	0.6	10	3.2	3 M - 1/2 QC	96	2438	56	114-042
48	1219	9	229	6.5	0.4	7.5	2.3	3 M - 1/2 QC	107	2717	72	114-048
54	1372	9	229	5	0.3	5.8	1.8	3 M - 1/2 QC	139	3530	90	114-054
60	1524	10	254	4.5	0.3	5.2	1.6	3 M - 1/2 QC	146	3708	104	114-060
66	1676	10	254	4	0.3	4.6	1.4	3 M - 1/2 QC	159	4038	124	114-066
72	1829	10	254	4	0.3	4.6	1.4	3 M - 1/2 QC	171	4343	146	114-072
84	2133	11	280	3	0.2	3.5	1.1	3 M - 1/2 QC	197	5004	195	114-084

*QC Quick connection

Custom configurations also available.

