

115 Series Multi-Flex™ Medium Duty Plugs Sizes: 2.5" to 72" With By-Pass

Pipe Diameter		By-Pass Connection		Maximum Inflation		**Pipeline Max. Head		Inflation Port*		Deflated Length		Shpg Wt lbs	Item Number		
in	mm	in	mm	in	npt	psig	bar	ft	m	in	npt	in	mm		
4	102	2.5	63	1/8	F	30	2.1	35	10.5	1/8 F - 1/4 QC	16	406	6	115-004	
6	152	3.0	76	1/8	F	30	2.1	35	10.6	1/8 F - 1/4 QC	19	482	10	115-006	
8	203	3.5	89	1/8	F	30	2.1	35	10.6	1/8 F - 1/4 QC	21	533	11	115-008	
10	254	3.5	89	1/8	F	30	2.1	35	10.6	1/8 F - 1/4 QC	26	660	13	115-010	
12	305	4.5	114	3/8	F	25	1.7	29	8.8	3/8 F - 1/4 QC	30	762	17	115-012	
15	381	5.5	140	3/4	F	25	1.7	29	8.8	3/8 F - 1/2 QC	34	864	24	115-015	
16	406	5.5	140	3/4	F	25	1.7	29	8.8	3/8 F - 1/2 QC	41	1041	28	115-016	
18	457	6.0	152	3/4	F	22	1.5	25	7.7	3/8 F - 1/2 QC	45	1143	32	115-018	
20	508	6.0	152	3/4	F	20	1.4	23	7.0	3/8 F - 1/2 QC	50	1270	35	115-020	
24	610	6.0	152	3/4	F	10	0.7	11	3.5	3/8 F - 1/2 QC	59	1498	38	115-024	
30	762	6.0	152	3/4	F	9	0.6	10	3.2	3/8 F - 1/2 QC	73	1854	46	115-030	
33	838	7.0	178	3/4	F	9	0.6	10	3.2	3/8 F - 1/2 QC	74	1879	50	115-033	
36	914	7.0	178	3/4	F	9	0.6	10	3.2	3/8 F - 1/2 QC	84	2133	54	115-036	
42	1067	8.0	203	3/4	F	9	0.6	10	3.2	3/8 F - 1/2 QC	96	2438	70	115-042	
48	1219	9.0	229	3/4	F	6.5	0.4	7.5	2.3	3/8 F - 1/2 QC	107	2717	90	115-048	
54	1372	9.0	229	3/4	F	5	0.3	5.8	1.9	3/8 F - 1/2 QC	134	3404	111	115-054	
60	1524	10.0	254	3/4	F	4.5	0.3	5.2	1.6	3/8 F - 1/2 QC	146	3708	127	115-060	
66	1676	10.0	254	3/4	F	4	0.3	4.6	1.4	3/8 F - 1/2 QC	159	4038	148	115-066	
72	1829	10.0	254	3/4	F	4	0.3	4.6	1.4	3/8 F - 1/2 QC	171	4343	180	115-072	

*QC Quick connection

Custom configurations also available

